

FTA-C300-16AO-TEST-Z**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

Analogue input/output direct FTAs for Honeywell C300 IOTAs.

Passive interfaces (FTA) for connecting the Honeywell C300 analog IOTAs.

- Clearly labelled: Same connector and position on the FTA and on the IOTA.
- 2 units may also be used for the digital IOTAs.
- Disconnecting plugs and test points (2mm in diameter) for voltage and current measurements.
- The FTAs incorporate an M4 connection for the shielding.
- Screw or tension clamp connection

General ordering data

| | |
|-----------------|---|
| Version | Interface, RS, 1-wire, Tension-clamp connection |
| Order No. | 1223030000 |
| Type | FTA-C300-16AO-TEST-Z |
| GTIN (EAN) | 4050118006575 |
| Qty. | 1 pc(s). |
| Delivery status | Discontinued |

FTA-C300-16AO-TEST-Z

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Depth | 95 mm | Depth (inches) | 3.74 inch |
| Height | 133 mm | Height (inches) | 5.236 inch |
| Width | 110 mm | Width (inches) | 4.331 inch |
| Net weight | 380 g | | |

Temperatures

| | | | |
|---------------------|-------------|-----------------------|-------------|
| Storage temperature | -40...60 °C | Operating temperature | -25...50 °C |
|---------------------|-------------|-----------------------|-------------|

Rated data UL

| | | | |
|--------------------------------|-------|--------------------------------|---------|
| Operating temperature UL, max. | 25 °C | Operating temperature UL, min. | 0 °C |
| Rated current I _N | 1 A | Rated voltage U _N | 24 V DC |

General data

| | | | |
|--------------------------------|----------------|----------------------------------|-----|
| LED status display per channel | No | Disconnection per channel | Yes |
| Voltage point of measurement | Yes | Current-measuring testpoint | Yes |
| Type of test point | Diameter: 2 mm | Switch | No |
| Fuse per channel | No | LED status of the supply voltage | No |
| Power supply fuse | No | | |

Connection data

| | | | |
|--------------------------------|----------------|-----------------------------|-------------------|
| Connection (field side) | LM2NZF 5.08mm | Connection on control side | SLDV-THR 5.08 |
| Number of poles (control side) | 32-pole female | Protective earth connection | M4 round terminal |
| Wiring system | 1-wire | | |

Ratings data

| | | | |
|-------------------|---------------|--------------------------|-----|
| Operating voltage | 24 V DC ± 10% | Max. current per channel | 1 A |
|-------------------|---------------|--------------------------|-----|

Insulation coordination (EN50178)

| | | | |
|-------------------------------|--------------|----------------------------|-----------|
| According to | DIN EN 50178 | Rated insulation voltage | ≤ 50 V DC |
| Surge voltage category | III | Pollution severity level | 2 |
| Pulse voltage test (1,2/50µs) | 0.8 kV | Insulation test voltage AC | 0.35 kV |

Connection field

| | | | |
|----------------------------------|--------------------------|------------------------------|----------------------|
| Clamping range, max. | 2.5 mm ² | Clamping range, min. | 0.13 mm ² |
| Flexible with sleeve, max. | 1.5 mm ² | Flexible with sleeve, min. | 0.25 mm ² |
| Flexible, max. H05(07) V-K | 1.5 mm ² | Flexible, min. H05(07) V-K | 0.2 mm ² |
| Max. wire cross-section, AWG | AWG 14 | Min. wire cross-section, AWG | AWG 24 |
| Sleeve with plastic collar, max. | 1.5 mm ² | Solid, max. H05(07) V-U | 2.5 mm ² |
| Solid, min. H05(07) V-U | 0.2 mm ² | Stripping length | 7.5 mm |
| Type of connection | Tension-clamp connection | | |

FTA-C300-16AO-TEST-Z

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Supply connection

| | | | |
|------------------------------|--------------------------|-----------------------------------|----------------------|
| Type of connection | Tension-clamp connection | Clamping range, min. | 0.13 mm ² |
| Clamping range, max. | 2.5 mm ² | Solid, min. H05(07) V-U | 0.2 mm ² |
| Solid, max. H05(07) V-U | 2.5 mm ² | Flexible, min. H05(07) V-K | 0.2 mm ² |
| Flexible, max. H05(07) V-K | 1.5 mm ² | Flexible with sleeve, max. | 1.5 mm ² |
| Flexible with sleeve, min. | 0.25 mm ² | Ferrule with plastic collar, max. | 1.5 mm ² |
| Wire cross-section, min. AWG | AWG 14 | Wire cross-section, max. AWG | AWG 24 |
| Stripping length | 7.5 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002780 | ETIM 7.0 | EC002780 |
| ETIM 8.0 | EC002780 | ETIM 9.0 | EC002780 |
| ETIM 10.0 | EC002780 | ECLASS 9.0 | 27-14-11-52 |
| ECLASS 9.1 | 27-14-11-52 | ECLASS 10.0 | 27-14-11-52 |
| ECLASS 11.0 | 27-14-11-52 | ECLASS 12.0 | 27-14-11-52 |
| ECLASS 13.0 | 27-14-11-52 | ECLASS 14.0 | 27-14-11-52 |
| ECLASS 15.0 | 27-14-11-52 | | |

Approvals

Approvals



| | |
|-----------------------|---|
| Approvals MAMID | https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319262/-T1z1mm-S800/ |
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate No. (UR) | E141197 |

Environmental Product Compliance

| | |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status | Compliant with exemption |
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | 2e4a427f-c282-4ebf-8ee2-8af7c9348f4e |

Downloads

| | |
|------------|--|
| Catalogues | Catalogues in PDF-format |
| Brochures | |

FTA-C300-16AO-TEST-Z

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

